



# element™

Patent Pending

*Pedigo's new IV stand features a number of unique design elements to further promote safety, organization and efficiency of IV fluid administration.*



## clearview™ technology™

High impact molded polymer IV hook assembly features six hooks for easy reading all IV bag labels from the front of the stand.

Built-in offset for IV piggybacking.

Smooth finish and easy to clean.



## clearstep™ technology™

Created with patient and staff safety in mind, the element's clearstep base is ergonomically designed for easy ambulation..



## interlockingbases™

The interlockingbases™ allow for multiple stands to be moved at one time by connecting the element™ together.

Designed for comfortable transport and storage of multiple stands.



P-1090-CV Infusion Pump Stand





**Adjustment**

Hand operated easygrip™ knob.

**Pole**

Stainless steel resists staining, corrosion and rusting.

**Base**

Five caster, 19 lbs. (9 kg) base offers improved stability.

**Casters**

Precision ball bearing sealed casters for ultra low rolling resistance.

**Footprint - 21.25 (54 cm)**

Small footprint allows unobstructed path while patient ambulates.

P-1090-CV Infusion Pump Stand

**SPECIFICATIONS**

element™	P-1090-CV	
<b>Weight</b>		
Overall Product Weight	26 lbs. (12 kg)	
Base Weight (with Casters)	19 lbs. (9 kg)	
<b>Weight Capacity (Maximum)</b>		
Hooks (each)	7 lbs. (3 kg)	
Offset Load (Base Tube)†	40 lbs. (18 kg)	
Total Load‡	90 lbs. (41 kg)	
Number of Pumps per Stand	2 (15 lbs. each)	
<b>Casters</b>		
5 Swivel Casters	3" (8 cm)	
<b>Height Adjustment</b>		
Low	74" (188 cm)	
High	122" (310 cm)	
<b>Base Diameter (Caster Centerline)</b>	21.25" (54 cm)	
<b>Number of Interlocking Stands (Max.)</b>	6	
<b>Accessories</b>		
Patient Handle	O2 Holder	Basket
Outlet Strip	Foley bag Hook	



The clearview™ hooks are ideal for IV piggybacking of primary and secondary bags with a full 10" of height difference between bags.



With a recess on each side of the base, emulating the natural shape of the foot, clearstep™ allows for safe ambulation.

† 40 lbs max applied at 6" off center, 3 ft off ground

‡ 90 lbs max applied at centerline of pole, 3 ft off ground